



| 序号 | 型号 (Type) | 料号 (PART NO) | 螺纹规格 Thread size |
|----|---------------------|--------------|---------------------|
| 1 | H10A-SF-1L-CV-2M20 | 19200100295 | M20 |
| 2 | H10A-SF-1L-CV-2PG16 | 19200100296 | PG16 |

- 技术参数:
- 材料: 压铸铝
 - 盖子材料: PC
 - 表面处理: 粉末喷涂
 - 颜色: Grey (灰色)
 - 温度范围: -40℃ - +125℃
 - 防护等级: IP65 (联锁状态, IEC 60529)
 - 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 金属 (铁) 镀锌
 - 出线方向: 侧出线
 - 出线孔数: 2
 - 螺纹规格: M/PG

- Technical specification:
- Material: Aluminium die-cast
 - Material, cover: PC
 - Surface: powder-coated
 - Colour: (grey)
 - Temperature range:
 - 40℃ - +125℃
 - Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
 - Locking element:
 - locking type: single locking latch
 - material: metal galvanized/nickel plating
 - Cable entry: side entry
 - No. of cable entries: 2
 - Thread size: M/PG

| | | | | | | | | |
|---|---|-------------------|------|--------|-----|--------|-------|--|
| 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD | | 图号 Drawing No: | | / | | | | |
| 产品代号 Part Code: H10A-SF-1L-CV-2M/2PG | | 产品料号 PART NO: | | / | | | | |
| Date: | 2018.08.16 | Scale | REV | Weight | Qty | Drawn: | SHEET | |
| | All Dimensions in mm Original Size DIN A 4 | 1:2 | HK-1 | / | / | Tang | 1/1 | |