



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H16B-TE-2L-M25	19300161431	M25
2	H16B-TE-2L-M32	19300161432	M32
2	H16B-TE-2L-PG21	09300161430	PG21

技术参数:  
 - 材料: 压铸铝  
 - 表面处理: 粉末喷涂  
 - 颜色: Grey (灰色)  
 - 温度范围: -40℃ - +125℃  
 - 防护等级: IP65 (联锁状态, IEC 60529)  
 - 联锁元件:

锁扣方式: 金属双扣  
 材料: 不锈钢  
 - 出线方向: 顶出线  
 - 出线孔数: 1  
 - 螺纹规格: M/PG

Technical specification:  
 - Material: Aluminium die-cast  
 - Surface: powder-coated  
 - Colour: (grey)  
 - Temperature range:  
   -40℃ - +125℃  
 - Degree of Protection: IP65  
 (acc.to IEC 60529 for coupled connector)  
 - Locking element:  
   locking type: double locking latch  
   material: stainless steel  
 - Cable entry: top entry  
 - No. of cable entries: 1  
 - Thread size: M/PG

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/			
产品代号 Part Code: H16B-TE-2L-M/PG		产品料号 PART NO:		/			
Date:	2018.09.16	Scale	REV	Weight	Qty	Drawn:	SHEET
	All Dimensions in mm Original Size DIN A 4	1:2	HK-1	/	/	Tang	1/1