



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H24B-TEH-4B-2M25	19300240466	M25
2	H24B-TEH-4B-2M32	19300240467	M32
3	H24B-TEH-4B-2PG16	09300240461	PG16
4	H24B-TEH-4B-2PG21	09300240462	PG21
5	H24B-TEH-4B-2PG29	09300240463	PG29

- 技术参数:
- 材料: 压铸铝
  - 表面处理: 粉末喷涂
  - 颜色: Grey (灰色)
  - 温度范围: -40°C - +125°C
  - 防护等级: IP65 (联锁状态, IEC 60529)
  - 出线方向: 顶出线
  - 出线孔数: 2
  - 螺纹规格: M/PG

- Technical specification:
- Material: Aluminium die-cast
  - Surface: powder-coated
  - Colour: (grey)
  - Temperature range: -40°C - +125°C
  - Degree of Protection: IP65 (acc.to IEC 60529 for coupled connector)
  - Cable entry: top entry
  - No. of cable entries: 2
  - Thread size: M/PG

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/			
产品代号 Part Code: H24B-TEH-4B-2M/2PG		产品料号 PART NO:		/			
Date:	2019.02.10	Scale	REV	Weight	Qty	Drawn:	SHEET
	All Dimensions in mm Original Size DIN A 4	1:1.5	HK-1	/	/	Tang	1/1