



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H32B-TE-2L-M32	19300320437	M32
2	H32B-TE-2L-M40	19300320438	M40
3	H32B-TE-2L-M50	19300320439	M50
4	H32B-TE-2L-PG29	09300320431	PG29
5	H32B-TE-2L-PG36	09300320432	PG36
6	H32B-TE-2L-PG42	09300320433	PG42

技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:

锁扣方式: 金属双扣

材料: 金属(铁)镀锌

- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M/PG

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range: -40℃ - +125℃
- Degree of Protection: IP65 (acc.to IEC 60529 for coupled connector)
- Locking element: locking type: double locking latch material: metal galvanized/nickel plating
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M/PG

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/				
产品代号 Part Code: H32B-TE-2L-M/PG		产品料号 PART NO:		/				
Date:	2019.03.10	Scale	REV	Weight	Qty	Drawn:	SHEET	
	All Dimensions in mm Original Size DIN A 4	1:3	HK-1	/	/	Tang	1/1	