



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H6B-SFH-1L-MCV-2M25	19300067296	M25
2	H6B-SFH-1L-MCV-2M32	19300061297	M32
3	H6B-SFH-1L-MCV-2PG21	09300062297	PG21
4	H6B-SFH-1L-MCV-2PG29	09300062298	PG29

技术参数:

- 材料: 压铸铝
- 盖子材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40°C - +125°C
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
  - 锁扣方式: 单扣
  - 材料: 金属 (铁) 镀锌
- 出线方向: 侧出线
- 出线孔数: 2
- 螺纹规格: M/PG
- 密封元件: NBR

Technical specification:

- Material: Aluminium die-cast
- Material, cover: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
  - 40°C - +125°C
- Degree of Protection: IP65  
(acc.to IEC 60529 for coupled connector)
- Locking element:
  - locking type: single locking latch
  - material: metal galvanized/nickel plating
- Cable entry: side entry
- No. of cable entries: 2
- Thread size: M/PG
- Hoods/Housings sealing: NBR

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/				
产品代号 Part Code: H6B-SFH-1L-MCV-2M/2PG		产品料号 PART NO:		/				
Date:	2018.08.16	Scale	REV	Weight	Qty	Drawn:	SHEET	
	All Dimensions in mm Original Size DIN A 4	1:2	HK-1	/	/	Tang	1/1	