

8		7		6		5		4		3		2		1					
技术参数 (DIN EN 61984)										REVISIONS									
插针数										REV		ECN		DESCRIPTION		DATE		DRFT	
额定电流										64+PE		10A		250V		4KV		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV		3		3	
绝缘电阻										≥10 ⁹ Ω		聚碳酸酯		UL94-V0		-40℃~+125℃		冷压连接	
温度范围										-40℃~+125℃		冷压连接		≥500					
插拔次数										≥500									
插针数										64+PE		10A		250V		4KV		3	
额定电流										10A		250V		4KV		3		3	
额定电压										10A		250V		4KV		3		3	
脉冲电压										10A		250V		4KV					