

8		7	6	5	4	3	2	1	
技术参数 (DIN EN 61984)					REVISIONS				
					REV	ECN	DESCRIPTION	DATE	DRFT
H	插针数	3							
	额定电流	40A							
	额定电压	690V							
	脉冲电压	8KV							
	污染等级	3							
	绝缘电阻	≥10 ¹⁰ Ω							
G	材料	聚碳酸酯							
	阻燃等级	UL94-V0							
	温度范围	-40℃~+125℃							
	接线方式	轴向螺栓连接							
F	插拔次数	≥500							
E									
D									
C									
B									
A									

浙江昊科电气有限公司 ZHEJIANG HAOK E ELECTRICAL CO., LTD										
产品代号 Part Code: HMK-003.1-F(2.5-8mm ²)					图号 Drawing No: /					
Date: 2021.04.24					REV		Weight		SHEET	
Scale 2:1					HK-1		/		1/1	
Qty					Drawn:					
Tang										

未注尺寸公差(mm)									
0 ~ ≤20	20 ~ ≤50	50 ~ ≤80	80 ~ ≤120	120 ~ ≤150	150 ~ ≤200	>200			
±0.15	±0.25	±0.35	±0.50	±0.70	±1.00	±1.50			

浙江昊科电气有限公司 ZHEJIANG HAOK E ELECTRICAL CO., LTD										
产品代号 Part Code: HMK-003.1-F(2.5-8mm ²)					图号 Drawing No: /					
Date: 2021.04.24					REV		Weight		SHEET	
Scale 2:1					HK-1		/		1/1	
Qty					Drawn:					
Tang										

未注尺寸公差(mm)									
0 ~ ≤20	20 ~ ≤50	50 ~ ≤80	80 ~ ≤120	120 ~ ≤150	150 ~ ≤200	>200			
±0.15	±0.25	±0.35	±0.50	±0.70	±1.00	±1.50			

浙江昊科电气有限公司 ZHEJIANG HAOK E ELECTRICAL CO., LTD										
产品代号 Part Code: HMK-003.1-F(2.5-8mm ²)					图号 Drawing No: /					
Date: 2021.04.24					REV		Weight		SHEET	
Scale 2:1					HK-1		/		1/1	
Qty					Drawn:					
Tang										