

8		7	6	5	4	3	2	1	
技术参数 (DIN EN 61984)		REVISIONS							
		REV							
		ECN							
		DESCRIPTION							
		DATE							
		DRFT							
H	插针数	3							
	额定电流	40A							
	额定电压	690V							
	脉冲电压	8kV							
	污染等级	3							
	绝缘电阻	≥10 ¹⁰ Ω							
G	材 料	聚碳酸酯							
	阻燃等级	UL94-V0							
	温度范围	-40℃~+125℃							
	接线方式	轴向螺栓连接							
F	插拔次数	≥500							
E									
D									
C									
B									
A									
8		7	6	5	4	3	2	1	

未注尺寸公差(mm)							
0 ~ ≤20	20 ~ ≤50	50 ~ ≤80	80 ~ ≤120	120 ~ ≤150	150 ~ ≤200	>200	
±0.15	±0.25	±0.35	±0.50	±0.70	±1.00	±1.50	

产品代号		浙江昊科电气有限公司		图号			
Part Code:		HMK-003.1-M(2.5-8mm ²)		Drawing No:			
Date:	2021.04.24	Scale	REV	Weight	Qty	Drawn:	SHEET
All Dimensions in mm		2:1	HK-1	/	/		1/1
Original Size DIN A 4							

未注尺寸公差(mm)							
0 ~ ≤ 20	20 ~ ≤ 50	50 ~ ≤ 80	80 ~ ≤ 120	120 ~ ≤ 150	150 ~ ≤ 200	>200	
± 0.15	± 0.25	± 0.35	± 0.50	± 0.70	± 1.00	± 1.50	

ZJK

浙江昊科电气有限公司
ZHEJIANG HAOKE ELECTRICAL CO., LTD

图号
Drawing No:

产品代号
Part Code: HMK-003.1-M(2.5-8mm²)

产品料号
PART NO:

Date:	2021.04.24	Scale	REV	Weight	Qty	Drawn:	SHEET
All Dimensions in mm Original Size DIN A 4		2:1	HK-1	/	/		1/1