


8		7	6	5	4	3	2	1		
技术参数 (DIN EN 61984)						REVISIONS				
插针数						REV	ECN	DESCRIPTION	DATE	DRAFT
额定电流						5				
额定电压						16A				
脉冲电压						500V				
污染等级						3				
依据UL/CSA的额定电压						600V				
绝缘电阻						≥10 ⁹ Ω				
材 料						聚碳酸酯				
阻燃等级						UL94-V0				
温度范围						-40℃~+125℃				
接线方式						弹片连接				
插拔次数						≥500				

34, 2						14, 6						34. 1																							

未注尺寸公差(mm)												
0 ~ ≤20	20 ~ ≤50	50 ~ ≤80	80 ~ ≤120	120 ~ ≤150	150 ~ ≤200	>200						
±0.15	±0.25	±0.35	±0.50	±0.70	±1.00	±1.50						

ZJRK 浙江昊科电气有限公司 ZHEJIANG HAOKO ELECTRICAL CO., LTD				图号 Drawing No:							
产品代号 Part Code: HME-005-FS				产品料号 PART NO:							
Date: 2021.04.24				Scale: 2:1		REV: HK-1		Weight: /		Qty: /	
All Dimensions in mm Original Size DIN A 4				REV: HK-1		Weight: /		Qty: /		Tang: /	
SHEET 1/1				Drawn: /		Tang: /		Qty: /		SHEET 1/1	



未注尺寸公差(mm)						
0 ~ ≤ 20	20 ~ ≤ 50	50 ~ ≤ 80	80 ~ ≤ 120	120 ~ ≤ 150	150 ~ ≤ 200	>200
± 0.15	± 0.25	± 0.35	± 0.50	± 0.70	± 1.00	± 1.50

			浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD			图号 Drawing No:		/
产品代号 Part Code:			HME-005-FS			产品料号 PART NO:		/
Date:	2021.04.24	Scale	REV	Weight	Qty	Drawn:		SHEET
	All Dimensions in mm Original Size DIN A 4	2:1	HK-1	/	/	Tang		1/1