




REVISIONS				
REV	ECN	DESCRIPTION	DATE	DRFT




4XM3 SCREW,RECOMMENDED
TIGHTENING TORQUE 0.5N.m
4XM3螺丝,推荐锁紧力矩0.5N.m



M5 SCREW,RECOMMENDED
TIGHTENING TORQUE 2.0N.m
M5螺丝,推荐锁紧力矩2.0N.m



面板安装开孔图
Panel cut out



技术参数:

插芯:

- 插针数: 46+PE
- 额定电流: 16A
- 额定电压: 500V
- 额定脉冲电压: 6kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V
- 绝缘阻抗: $\geq 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: ≥ 500

插针:

- 接线方式：冷压连接
- 材料：铜合金
- 表面处理：
 - 镀银
 - 银金
- 接触电阻： $\leq 1\text{m}\Omega$
- 线径范围： $0.14\sim 4.0\text{mm}^2(26\sim 12\text{AWG})$
- 剥线长度：7.5mm
- 工具：
 - 冷压钳：
TL02G(0.14~4mm²)
 - 退针器：TL01

Technical specification:

Inserts:

- No. of contact: 46+PE
- Rated current: 16A
- Rated voltage: 500V
- Rated impulse voltage: 6kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V
- Insulation resistance: $> 10^{10} \Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: > 500

Contacts:

- Terminal: crimp terminal
- Material: copper alloy
- Surface:
 - Hard-silver plated
 - Hard-gold plated
- Contact resistance: $< 1\text{m}\Omega$
- Wire gauge: 0.14–4.0mm² (26–12 AWG)
- Stripping length: 7.5mm
- Tools:
 - Crimp contact tool: TL02G(0.14–4mm²)
 - Contact removal tool: TL01

 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD					图号 Drawing No:		／		
产品代号 Part Code:					产品料号 PART NO:		09320463001		
Date:		2025.01.14	Scale	REV	Weight	Qty	Drawn:		SHEET
		All Dimensions in mm Original Size DIN A 4		HK-1	／	／	Tang		1/1