



序号	型号 (Type)	料号(PART NO)	螺纹规格 Thread size
1	H24B-SF-2L-M25	19300241231	M25
2	H24B-SF-2L-PG21	09300241230	PG21



技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ ~ +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:


锁扣方式：金属双扣

材料：金属（铁）镀锌

- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M/PG
- 密封元件: NBR

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
 - 40°C - +125°C
- Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - locking type: double locking latch
 - material: metal galvanized/nickel plating
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M/PG
- Hoods/Housings sealing: NBR



 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD					图号 Drawing No:		/		
产品代号 Part Code: H24B-SF-2L-M/PG					产品料号 PART NO:		/		
Date:		2018.08.10	Scale	REV	Weight	Qty	Drawn:		SHEET
		All Dimensions in mm Original Size DIN A 4	1:1	HK-1	/	/	Tang		1/1