




序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H10B-SEH-4B-M25	19300100526	M25
2	H10B-SEH-4B-M32	19300100527	M32
3	H10B-SEH-4B-PG21	09300100522	PG21
4	H10B-SEH-4B-PG29	09300100523	PG29



技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M/PG

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
-40℃ - +125℃
- Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M/PG

ZJK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD					图号 Drawing No:		/	
产品代号 Part Code: H10B-SEH-4B-M/PG					产品料号 PART NO:		/	
Date:	2026.08.01	Scale	REV	Weight	Qty	Drawn:		SHEET
	All Dimensions in mm Original Size DIN A 4		1:1.5	HK-1	/	Tang		1/1