

序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H16B-CCTH-2L-M25	19300160736	M25
2	H16B-CCTH-2L-M32	19300160737	M32
3	H16B-CCTH-2L-M40	19300160738	M40
4	H16B-CCTH-2L-PG21	09300160730	PG21
5	H16B-CCTH-2L-PG29	09300160731	PG29

技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ ~ +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:

锁扣方式: 金属双扣

材料: 金属 (铁) 镀锌

- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M/PG
- 密封元件: NBR

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
-40℃ ~ +125℃
- Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
locking type: double locking latch
material: metal galvanized
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M/PG
- Hoods/Housings sealing: NBR

ZJHK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD					图号 Drawing No:		/	
产品代号 Part Code: H16B-CCTH-2L-M/PG					产品料号 PART NO:		/	
日期 Date:	2025.10.13	比例 Scale	版本 REV	重量 Weight	数量 Qty	绘图 Drawn		页 SHEET
		All Dimensions in mm Original Size DIN A 4		1.5:1	HK-1	/	/	Tang
								1/1