

| 序号 | 型号 (Type)        | 料号 (PART NO) | 螺纹规格<br>Thread size |
|----|------------------|--------------|---------------------|
| 1  | H16B-TEH-2L-M32  | 19300160437  | M32                 |
| 2  | H16B-TEH-2L-M40  | 19300160438  | M40                 |
| 3  | H16B-TEH-2L-PG21 | 09300160430  | PG21                |
| 4  | H16B-TEH-2L-PG29 | 09300160431  | PG29                |

技术参数:  
- 材料: 压铸铝  
- 表面处理: 粉末喷涂  
- 颜色: Grey (灰色)  
- 温度范围: -40℃ - +125℃  
- 防护等级: IP65 (联锁状态, IEC 60529)  
- 联锁元件:  
    锁扣方式: 金属双扣  
    材料: 金属 (铁) 镀锌  
- 出线方向: 顶出线  
- 出线孔数: 1  
- 螺纹规格: M/PG  
- 密封元件: NBR

Technical specification:  
- Material: Aluminium die-cast  
- Surface: powder-coated  
- Colour: (grey)  
- Temperature range:  
    -40℃ - +125℃  
- Degree of Protection: IP65  
  (acc.to IEC 60529 for coupled connector)  
- Locking element:  
    locking type: double locking latch  
    material: metal galvanized  
- Cable entry: top entry  
- No. of cable entries: 1  
- Thread size: M/PG  
- Hoods/Housings sealing: NBR

|                                                     |            |             |           |              |                   |             |   |            |
|-----------------------------------------------------|------------|-------------|-----------|--------------|-------------------|-------------|---|------------|
| ZJK 浙江昊科电气有限公司<br>ZHEJIANG HAOKE ELECTRICAL CO.,LTD |            |             |           |              | 图号<br>Drawing No: |             | / |            |
| 产品代号<br>Part Code: H16B-TEH-2L-M/PG                 |            |             |           |              | 产品料号<br>PART NO:  |             | / |            |
| 日期<br>Date:                                         | 2025.10.13 | 比例<br>Scale | 版本<br>REV | 重量<br>Weight | 数量<br>Qty         | 绘图<br>Drawn |   | 页<br>SHEET |
| All Dimensions in mm<br>Original Size DIN A 4       |            | 1.5:1       | HK-1      | /            | /                 | Tang        |   | 1/1        |