




87654321

序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H16A-CCT-1L-PG16	09200161751	PG16
2	H16A-CCT-1L-M20	19200161730	M20

技术参数:
- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 锁扣方式: 单扣
 材料: 金属 (铁) 镀锌
- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M/PG

Technical specification:
- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
 -40℃ - +125℃
- Degree of Protection: IP65
 (acc.to IEC 60529 for coupled connector)
- Locking element:
 locking type: single locking latch
 material: metal galvanized
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M/PG

ZJK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD					图号 Drawing No:		/		
产品代号 Part Code: H16A-CCT-1L-M&PG					产品料号 PART NO:		/		
Date:	2025.07.30	Scale	REV	Weight	Qty	Drawn:		SHEET	
	All Dimensions in mm Original Size DIN A 4		1:2	HK-1	/	Tang		1/1	



87654321