







面板开孔图
panel cut out

- 技术参数:
- 材料: 压铸铝
 - 表面处理: 粉末喷涂
 - 颜色: Grey (灰色)
 - 温度范围: -40℃ - +125℃
 - 防护等级: IP65 (联锁状态, IEC 60529)
 - 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 不锈钢
 - 出线方向: 侧出线
 - 出线孔数: 1
 - 螺纹规格: M20
- Technical specification:
- Material: zinc die-cast
 - Surface: powder-coated
 - Colour: (grey)
 - Temperature range:
 - 40℃ - +125℃
 - Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
 - Locking element:
 - locking type: single locking latch
 - material: stainless steel
 - Cable entry: side entry
 - No. of cable entries: 1
 - Thread size: M20

ZJK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD						图号 Drawing No:		/	
产品代号 Part Code: H3A-SF-1L-M20						产品料号 PART NO:		19200031252	
Date:	2018.08.10	Scale	REV	Weight	Qty	Drawn:			SHEET
	All Dimensions in mm Original Size DIN A 4		1:1	HK-1	/	Tang			1/1